



## H6062A1000

HumidiPRO Digital Humidity Control

### Overview

Easy to use, digital control of your home's humidification or dehumidification. HumidiPRO™ will automatically adjust settings for changes in outdoor temperature to ensure no condensation will appear in your home (window protection).

### Features

- Automatic humidification (window protection) with included outdoor sensor
- Manual humidification control
- Manual dehumidification control
- Dehumidifier compressor protection
- Large, digital backlit display
- Simple, intuitive programming
- RH% and outdoor temperature calibration
- Adjustable high and low range stops (10-90%)
- Automatically detects presence of outdoor sensor to set control to Automatic or Manual Mode

### Product Specifications

|                                 |                                                                                  |
|---------------------------------|----------------------------------------------------------------------------------|
| Dimensions (in.)                | 3 7/16 in. high x 4 1/2 in. wide x 1 5/16 in. deep                               |
| Dimensions (mm)                 | 86 mm x 114 mm x 33 mm                                                           |
| Temperature Range (F)           | -20 F to +120 F                                                                  |
| Includes                        | HumidiPRO Control, Outdoor Sensor, Mounting Hardware                             |
| Used With                       | Whole Home Humidifiers or Dehumidifiers                                          |
| Item Type                       | Product                                                                          |
| Mounting                        | Return Duct (Recommended) or Wall Mount                                          |
| Frequency                       | 50 Hz; 60 Hz                                                                     |
| Operating Humidity Range (% RH) | Manual Mode: 10% to 90% RH% (Adjustable) Auto Mode: 10% to 60% RH% (35% Default) |
| Voltage                         | 24 Vac                                                                           |
| Type                            | Humidistat/Dehumidistat                                                          |
| Color                           | Premier White®                                                                   |
| Differential                    | 4% to 6% RH                                                                      |