

VE N SERIES



Dual Voltage (110-220V/50-60Hz)

Power plug

make this connection with different power plugs easily

Power supply conversion switch

make sure this switch is set on the right place before your operation: 110V or 220V



Dual Stage

Model		VE215ND	VE225ND	VE245ND
Flow Rate	50Hz	1.5 CFM	2.5 CFM	4.5 CFM
		42 L/min	70 L/min	128 L/min
	60Hz	1.8 CFM	3.0 CFM	5.0 CFM
		50 L/min	84 L/min	142 L/min
Ultimate Vacuum	Partial Pressure	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa
	Total Pressure	15 micron	15 micron	15 micron
Power		1/4 HP	1/3 HP	1/2 HP
Inlet Port		1/4" Flare	1/4" Flare	1/4"&3/8" Flare
Oil Capacity		200 ml	200 ml	325 ml
Dimensions		318x124x234 mm	318x124x234 mm	338x138x244 mm
Weight		8.5 Kg	8.5 Kg	10.4 Kg

Model		VE260ND	VE280ND	VE2100ND
Flow Rate	50Hz	6.0 CFM	8.0 CFM	10.0 CFM
		170 L/min	226 L/min	283 L/min
	60Hz	7.0 CFM	9.0 CFM	12.0 CFM
		198 L/min	254 L/min	340 L/min
Ultimate Vacuum	Partial Pressure	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa
	Total Pressure	15micron	15 micron	15 micron
Power		3/4 HP	1 HP	1 HP
Inlet Port		1/4"&3/8" Flare	1/4"&3/8" Flare	1/4"&3/8" Flare
Oil Capacity		580 ml	500 ml	590 ml
Dimensions		395x145x257 mm	395x145x257 mm	395x145x257 mm
Weight		15.8 Kg	16.2 Kg	16.7 Kg