



H600A1014

24/120/240Vac Wall mount Humidistat,Gray

Product Info

Overview

Mechanical humidity controllers provide automatic control of humidifiers and dehumidifiers or ventilators in central heating and air conditioning systems.

Features

- Fully enclosed, SPST, snap-acting, dust-proof switch are designed for wall or surface duct mounting
- H8909 and H46 models include Positive ON-OFF settings permit manual operation of controlled equipment.
- H600 models have a removable setting knob prevents tampering

Product Specifications

Dimensions (in.)	6 3/16 in. high x 3 3/8 in. wide x 2 1/4 in. deep
Dimensions (mm)	157 mm high x 86 mm wide x 57 mm deep
Temperature Range (F)	50 F to 125 F
Temperature Range (C)	10 C to 52 C
Mounting	Wall mount
Electrical Ratings	Humidifier Contacts--120 Vac, Full Load: 4.4A; 120 Vac, Locked Rotor: 26.4A; 120 Vac; Resistive: 12A; 240 Vac, Full Load: 2.2A; 240 Vac, Locked Rotor: 13.2A; 240 Vac, Resistive: 6A. Dehumidifier Contacts--120 Vac, Full Load: 7.5A; 120 Vac, Locked Rotor: 3
Tradeline Value	Tradeline
Operating Humidity Range (% RH)	20 to 80% RH
Voltage	120 Vac,24 Vac,240 Vac
Color	Gray
Differential	5% RH