

L Series Recovery Unit



Light • Fast

One Key Operation

- Easy to use

Twin Cylinder

- Faster recovery

Oil-free Compressor

- Suitable for all commonly used refrigerants

Self-purge Function

- Prevent mixing of various refrigerants

High Pressure Protection

- Safe to use

Model		VRR24L-R32			VRR24LOS-R32		
Refrigerant		Categories III : R12, R134a, R401C, R500, 1234fy Categories IV : R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 Categories V : R402A, R404A, R407A, R407B, R410A, R507, R32					
Power Supply		220V-240V~/50-60Hz	115V~/60Hz		220V-240V~/50-60Hz	115V~/60Hz	
Motor		1 HP	1 HP		1 HP	1 HP	
Motor Speed		1450 rpm/1750 rpm	1750 rpm		1450 rpm/1750 rpm	1750 rpm	
Maximal Current Draw		5 A	10 A		5 A	10 A	
Compressor		Oil-less, Air-cooled, Piston style					
Automatic Safety Shut-Off		38.5bar/3850kPa(558psi)					
Recovery Rate (kg/min)		Categories III	Categories IV	Categories V	Categories III	Categories IV	Categories V
	Vapor	0.40	0.50	0.50	0.40	0.50	0.50
	Liquid	3.00	3.50	3.50	3.00	3.50	3.50
	Push/Pull	7.50	8.50	9.50	7.50	8.50	9.50
Operating Temperature		0°C-40°C					
Dimensions		450×250×355 mm					
Weight		13.5 kg			14.7 kg		