

Job Information		Technical Data Sheet
Job Name	WSHP - List Price STOCK	
Date	10/31/2016	
Submitted By	Generafrio S.A.C.	
Software Version	04.90	
Unit Tag	48 000BTU	



Unit Overview							
Model Number	Voltage V/Hz/Phase	Air Flow CFM	Fluid Flow gpm	Cooling Capacity Btu/hr	Cooling Efficiency EER @ design	Heating Capacity Btu/hr	Heating Efficiency COP @ design
669809800	208-230/60/1	1600	12.30	48379	13.32	60202	4.63

Unit	
Model Number:	669809800
Unit Type:	Enfinity - Horizontal, Geothermal Range
Unit Construction:	Fiberglass Insulation
Approval:	ETL, CETL, ARI
Refrigerant Type	R-410A
Refrigerant Weight	61.0 oz

Unit Performance									
Air & Water Flow									
Airflow		Total External Static Pressure	Fluid Flow			Fluid Type	Fluid Pressure Drop		
1600 CFM		0.60 inH ₂ O	12.30 gpm / 3.08 gpm/ton			Water	16.02 ft H ₂ O		
Cooling Performance									
Fluid Temperature		Air Temperature				Capacity		Heat of Rejection Btu/hr	EER @ design
Entering °F	Leaving °F	Entering		Leaving		Total Btu/hr	Sensible Btu/hr		
		Dry Bulb °F	Wet Bulb °F	Dry Bulb °F	Wet Bulb °F				
85.0	94.9	80.0	67.0	59.7	57.1	48379	34555	60777	13.32
Heating Performance									
Fluid Temperature		Air Temperature		Capacity	Heat of Absorption Btu/hr	COP @ design			
Entering °F	Leaving °F	Entering Dry Bulb °F	Leaving Dry Bulb °F	Total Btu/hr					
70.0	62.3	70.0	104.9	60202	47219	4.63			


Electrical			
Unit Voltage	Minimum Voltage	Total Unit MCA	Total Unit Full Load Current
208-230/60/1	197 V	22.60 A	19.00 A
Compressor RLA	Compressor LRA	Motor FLA	Maximum Recommended Fuse Size / HACR Breaker Size
14.50 A	98.0 A	4.50 A	35 A

Physical						
Unit						
Length	Height	Width	Weight		Connections	
			Shipping	Operating	Water, FPT	Condensate, FPT
52.00 in	23.00 in	28.00 in	319 lb	298 lb	0.75	0.75 in
Cabinet						
Construction Type			Color			
Fiberglass Insulation			Galvanized			
Fan					Controls	
Type	Motor		Drive		Type	
	Type	Horsepower	Type	Type		
DWDI Centrifugal	Standard PSC	0.750 hp	Direct		Microtech III - Standalone	
Airstream						
Air			Filter			
Discharge		Return		(Quantity) Height x Width x Depth		
Straight Discharge		Left Hand Return Air		(2) 16 in x 22.5 in x 1 in		

Options	
Heating	
Heat Exchanger:	Copper Inner Tube / Steel Outer Tube
Controls	
Control Transformer:	50VA Control Transformer

Warranty	
Unit Warranty:	Standard

AHRI Certification



All equipment is rated and certified in accordance with AHRI / ISO 13256-1 and tested, investigated, and determined to comply with the requirements of the standards for Heating and Cooling Equipment UL-1995 for the United States and CAN/CSA-C22.2 NO.236 for Canada.

Accessories	
Optional	
Part Number	Description
668375401	Non-Programmable, 2-Stage (2H/2C)