

Suit for
R32

GF GENERAFRIO
LÍDERES EN SISTEMAS DE AIRE ACONDICIONADO Y REFRIGERACIÓN

VALUE
VALUE Creates Value

Making Your Job More Enjoyable

VRR36C4

Recovery Unit



Digital Backlit Display



Purge Function



Brushless DC Technology



Oil-Free Compressors



3 High-Speed Cooling Fans



4-Cylinder

Fastest · Most Powerful

4-Cylinder

- More powerful

Large Digital Display

- Easy-to-read large LCD display
- Backlit for clarity

Super-Efficient Condenser

- Over-sized micro-channel condenser
- 3 cooling fans

Dual Oil-Free Compressors

- Suitable for all commonly used refrigerants

Brushless DC Motor

- More efficient

Model		VRR36C4		
Refrigerant		Categorys III : R12, R134a, R401C, R500, 1234yf Categorys IV : R22, R401A, R401B, R402B, R407C, R407D, R408A,R409A,R411A R411B,R412A,R502,R509 Categorys V : R402A,R404A,R407A,R407B,R410A,R507,R32		
Power Supply		220~240V~50/60Hz	115V~50/60Hz	
Motor		Brushless DC motor 1.5HP		
Motor Speed		3000 rpm		
Maximal Current Draw		8.5 A	12 A	
Compressor		Oil-less, Air-cooled, Piston style		
Automatic Safety Shut-Off		38.5bar/3850kPa(558psi)		
Recovery Rate (kg/min)		Categorys III	Categorys IV	Categorys V
	Vapor	0.55	0.73	0.72
	Liquid	4.20	5.78	7.63
	Push/pull	8.10	9.00	9.90
Operating Temperature		0 °C-40 °C		
Dimensions		410×275×300 mm		
Weight		19 kg		