

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	45	Displacement (in^3/Rev):	3.84
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):	
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	9.70
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.80
Capacity (BTU/hr)	67000	83000	Overall Height (in):	17.40
Power (W):	6220	4370	Mounting Length (in):	7.50
Current (Amps):	9.1	7	Mounting Width (in):	7.50
EER(BTU/Wh):	10.8	19	Mounting Height (in):	18.20
Mass Flow (lbs/hr):	990	1030	Suction Size (in),Type:	7 / 8 Stub
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	75 Avg	80 Max	Initial Oil Charge (oz):	57
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	56
Record Date:	2004-03-02		Oil Type:	3MA
			Net Weight (lbs):	88.0
			Internal Free Volume (in^3):	264.5
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	75	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	16.5					
Max Operating Current (Amps):	13.00					
RLA, MCC/1.4(use for contactor selection)(Amps):	11.8					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	10.6					
RPM:	3500					
Box IP :	21					
UL File No:	SA2337-19930726					
UL File Date:	1993-07-26					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	460	3	60	Air Conditioning